

HAY X LIBERTY MATIN WALL

PRODUCT FACT SHEET



MATIN WALL


DESIGN BY INGA SEMPÉ, 2024

Featuring Liberty's distinctive floral print on the Matin Shade's classic pleated construction, the Liberty Matin Wall Lamp brings together two iconic designs in a poetic and timeless expression. The elegant shade is attached to a wall-mounted steel bracket that can be angled to create an ambient uplight as well as directional downlight. The lamp brings an inviting atmosphere to most rooms in the home and comes in different sizes and selected Liberty prints.


HIGHLIGHTS

- Part of a progressive and technologically advanced lighting collection.
- A family of contemporary table, ceiling, wall, and floor lamps.
- Elegant wall-mounted lamp with a steel wire bent frame, paired with Liberty's distinctive floral print.
- Shares the same shades as the table lamp variants and can easily be changed.
- The head of the lamp has an adjustable angle to direct light up or down.
- CE approved.
- Integrated LED light source ensuring a life span of at least 25,000 hours of use.
- Inline step dimmer.
- Available in two sizes and suitable for both private and office environments.

DIMENSIONS



MATIN WALL 300
WIDTH 30 CM
DEPTH 25 CM
HEIGHT 30 CM



MATIN WALL 380
WIDTH 38 CM
DEPTH 25 CM
HEIGHT 38 CM

MATERIALS

SHADE

Cotton fabric laminated to a PVC sheet.
Black top screw in injection moulded ABS.

BODY

Bent steel wire with polished brass finish, precision cast steel counter weight and injection moulded ABS.

CORD

Black silicone cable.

INLINE SWITCH

Injection moulded ABS.

COLOUR & FINISH

Please note that the colour codes are indicative.

		SIZE	
		Ø300	Ø380
SHADE COLOUR			
LIBERTY MITSU		●	●
LIBERTY BETSY ANN		●	●
LIBERTY ED		●	●
LIBERTY ROS		●	
LIBERTY CHERRY DROP		●	

TECHNICAL SPECIFICATIONS


LIGHT SOURCE Integrated LED, 5W, 150lm, 2800K warm white	DIMMABLE Yes	POWER SUPPLY 220-240V AC at 50/60Hz	IP 20	CORD LENGTH 200 cm	SWITCH Inline step dimmer. Located 50 cm from lamp base.
--	------------------------	---	-----------------	------------------------------	--

TEST SPECIFICATIONS*

FLUX (LUMENS) 150lm	CCT (KELVIN) 2800K, warm white	CRI (1-100) 85
-------------------------------	--	--------------------------

*Photometrics and the specification shown is taken using the integrated LED bulb fitted in the production luminaire.

PHOTOMETRICS



CERTIFICATES

CE APPROVED

This product has been assessed and complies with the essential requirements of the relevant European directives.



Tested according to the following european EN / IEC standards which relate specifically to electrical lighting products including

- EN 55015:2013 (radio disturbance)
- EN 61547:2009 (EMC immunity)
- EN 61000-3-2:2014 (EMC compatibility)
- EN 61000-3-3:2013 (EMC compatibility)
- EN 60598-2-4:1997 (portable luminaires)
- EN 60598-1:2015 (general requirements)
- EN 62493:2010 (human exposure to EMC)

COUNTRY OF ORIGIN

China

DOWNLOADS

Packshots and lifestyle photos, 2D / 3D files, care and maintenance, instructions, test certificates, product fact sheets, and product presentations are available in our Digital Library at hay.com.

[LINK TO DIGITAL LIBRARY](#)